





Withdrawal items

Picture	Series	LW size Typ. (mm)	T size Max. (mm)	L Range (uH)
	LQW2BH	2.0x1.5	1.78	3.3-470nH



Promotion items (Recommend)

Picture	Series	LW size Typ. (mm)	T size Max. (mm)	L Range (uH)
	LQW2BA	2.09x1.53	1.52	3.2-200nH
	LQW2UA	2.62x2.45	2.03	12-4700nH

	LQW2BH Series				LQW2BA Series				LQW2UA Series			
	<p>外觀寸法</p>  <p>ランド寸法</p> 				<p>外觀寸法</p>  <p>ランド寸法</p> 				<p>外觀寸法</p>  <p>ランド寸法</p> 			
Size	2.0x1.5 / H=1.78 max.				2.09x1.53 / H=1.52 max.				2.62x2.45 / H=2.03 max.			
Inductance(nH)	Q	RDC(Ω)	Rated Current(mA)	Q	RDC(Ω)	Rated Current(mA)	Q	RDC(Ω)	Rated Current(mA)	Q	RDC(Ω)	Rated Current(mA)
3.2	-	-	-	95	0.02	3800	-	-	-	-	-	-
3.3	10	0.05	910	-	-	-	-	-	-	-	-	-
3.6	-	-	-	75	0.05	2000	-	-	-	-	-	-
6.8	20	0.11	680	90	0.03	3000	-	-	-	-	-	-
7.5	-	-	-	85	0.04	2400	-	-	-	-	-	-
8.2	20	0.12	630	80	0.09	1500	-	-	-	-	-	-
10	30	0.03	1320	-	-	-	-	-	-	-	-	-
11	-	-	-	80	0.04	2400	-	-	-	-	-	-
12	30	0.11	680	80	0.04	2400	50	0.09	1000	-	-	-
13	-	-	-	80	0.04	2400	-	-	-	-	-	-
15	30	0.12	630	70	0.12	1500	-	-	-	-	-	-
18	30	0.10	690	85	0.05	2200	50	0.11	1000	-	-	-
20	-	-	-	85	0.05	2200	-	-	-	-	-	-
22	30	0.09	720	85	0.07	1900	55	0.12	1000	-	-	-
24	-	-	-	75	0.15	1400	-	-	-	-	-	-
27	40	0.17	540	85	0.07	2000	55	0.13	1000	-	-	-
33	40	0.15	570	75	0.12	1500	60	0.14	1000	-	-	-
36	-	-	-	75	0.08	1900	-	-	-	-	-	-
39	40	0.09	730	75	0.08	1900	60	0.15	1000	-	-	-
43	-	-	-	75	0.12	1550	-	-	-	-	-	-
47	40	0.23	450	70	0.20	1250	65	0.16	1000	-	-	-
51	-	-	-	75	0.11	1800	-	-	-	-	-	-
56	40	0.26	430	70	0.18	1250	65	0.18	1000	-	-	-
62	-	-	-	70	0.12	1650	-	-	-	-	-	-
68	40	0.23	460	70	0.20	1250	65	0.20	1000	-	-	-
75	-	-	-	68	0.28	1100	-	-	-	-	-	-
82	40	0.42	320	70	0.24	1200	60	0.22	1000	-	-	-
91	-	-	-	70	0.21	1300	-	-	-	-	-	-
100	40	0.38	350	66	0.35	1050	60	0.56	650	-	-	-
110	-	-	-	57	0.38	970	-	-	-	-	-	-
120	40	0.40	320	57	0.38	970	60	0.65	650	-	-	-
130	-	-	-	56	0.42	950	-	-	-	-	-	-
150	30	0.47	390	58	0.46	930	45	0.70	580	-	-	-
160	-	-	-	53	0.46	930	-	-	-	-	-	-
180	35	0.71	250	53	0.58	800	45	0.77	620	-	-	-
200	-	-	-	53	0.63	750	-	-	-	-	-	-
220	35	0.70	240	-	-	-	45	0.84	500	-	-	-
270	15	2.0	190	-	-	-	45	0.91	500	-	-	-
330	15	2.2	180	-	-	-	45	1.05	450	-	-	-
390	15	2.5	170	-	-	-	45	1.12	470	-	-	-
470	15	2.8	160	-	-	-	45	1.19	470	-	-	-