

PT 00008957 PN List 1135Items

[PT] Withdrawal of Large case size MLCC Products (100V or less)

Current Murata PN	Proposed Alternative Murata PN	Deviations
GCM43EC71C106KA02	GCM21BC71C106KE36	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 2012M(0805inch) •T size(Max):2.70mm to 1.45mm
GCM43ER11E475KA01	GCM31CR71E475KA55	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 3216M(1206inch) •T size(Max):2.70mm to 1.80mm • Temperature characteristics:R to X7R
GCM43RR11H334KA01	GCM188D71H105KE36	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 1608M(0603inch) •T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T •Capacitance:330000pF to 1.0uF
GCM43RR11H474KA01	GCM188D71H105KE36	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 1608M(0603inch) •T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T •Capacitance:470000pF to 1.0uF
GCM43ER11H225KA01	GCM21BD71H225KE36	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 2012M(0805inch) •T size(Max):2.70mm to 1.45mm • Temperature characteristics:R to X7T
GCM43ER11H225MA01	GCM21BD71H225KE36	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 2012M(0805inch) •T size(Max):2.70mm to 1.45mm • Temperature characteristics:R to X7T • Capacitance Tolerance:±20% to ±10%
GCM43ER71E475KA51	GCM31CR71E475KA55	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 3216M(1206inch) •T size(Max):2.70mm to 1.80mm
GCM43ER71E475MA37	GCM31CR71E475MA55	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 3216M(1206inch) •T size(Max):2.70mm to 1.80mm
GCM43RR71H474KA02	GCM188D71H105KE36	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 1608M(0603inch) •T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T •Capacitance:470000pF to 1.0uF
GCM43ER71H225KA02	GCM21BD71H225KE36	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 2012M(0805inch) •T size(Max):2.70mm to 1.45mm • Temperature characteristics:X7R to X7T
GCM43NR72A104KA01	GCM21BR72A104KA37	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm
GCM43RR72A154KA01	GCM21BC72A105KE36	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 2012M(0805inch) •T size(Max):2.00mm to 1.45mm • Temperature characteristics:X7R to X7S •Capacitance:150000pF to 1.0uF
GCM43RR72A224KA01	GCM21BC72A105KE36	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 2012M(0805inch) •T size(Max):2.00mm to 1.45mm • Temperature characteristics:X7R to X7S •Capacitance:220000pF to 1.0uF
GCM55RR11H684KA01	GCM188D71H105KE36	<ul style="list-style-type: none"> •LW size:5750M(2220inch) to 1608M(0603inch) •T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T •Capacitance:680000pF to 1.0uF
GCM55RR11H105KA01	GCM188D71H105KE36	<ul style="list-style-type: none"> •LW size:5750M(2220inch) to 1608M(0603inch) •T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T
GCM55RR72A334KA01	GCM21BC72A105KE36	<ul style="list-style-type: none"> •LW size:5750M(2220inch) to 2012M(0805inchi) •T size(Max):2.00mm to 1.45mm • Temperature characteristics:X7R to X7S •Capacitance:330000pF to 1.0uF
GCM55RR72A474KA01	GCM21BC72A105KE36	<ul style="list-style-type: none"> •LW size:5750M(2220inch) to 2012M(0805inchi) •T size(Max):2.00mm to 1.45mm • Temperature characteristics:X7R to X7S •Capacitance:470000pF to 1.0uF
GRM43EB11C226KE01	GRM319R61C226KE15	<ul style="list-style-type: none"> •LW size:4532M(1812inch) to 3216M(1206inch) •T size(Max):2.70mm to 0.95mm • Temperature characteristics:B to X5R

GRM43EB11C226KE01	GRM219R61C226ME15	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.00mm • Temperature characteristics:B to X5R • Capacitance Tolerance:±10% to ±20%
GRM43EB11C226ME01	GRM219R61C226ME15	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.00mm • Temperature characteristics:B to X5R
GRM43MB11H333KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X7R • Capacitance:33000pF to 47000pF
GRM43MB11H333MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X7R • Capacitance:33000pF to 47000pF
GRM43MB11H393KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X7R • Capacitance:39000pF to 47000pF
GRM43MB11H473KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X7R
GRM43MB11H473MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X7R
GRM43MB11H563KA01	GRM155R61H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:56000pF to 100000pF
GRM43MB11H683KA01	GRM155R61H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:68000pF to 100000pF
GRM43MB11H683MA01	GRM155R61H104ME14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:68000pF to 100000pF
GRM43MB11H823KA01	GRM155R61H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:82000pF to 100000pF
GRM43MB11H104KA01	GRM155R61H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R
GRM43MB11H104MA01	GRM155R61H104ME14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R
GRM43MB11H124KA01	GRM155R61H224KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:120000pF to 220000pF
GRM43NB11H154KA01	GRM155R61H224KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.50mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:150000pF to 220000pF
GRM43NB11H154MA01	GRM155R61H224ME01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.50mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:150000pF to 220000pF
GRM43NB11H184KA01	GRM155R61H224KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.50mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:180000pF to 220000pF
GRM43RB11H224KA01	GRM155R61H224KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):2.00mm to 0.55mm • Temperature characteristics:B to X5R
GRM43RB11H224MA01	GRM155R61H224ME01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):2.00mm to 0.55mm • Temperature characteristics:B to X5R

GRM43RB11H274KA01	GRM155R61H474KE11	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):2.00mm to 0.60mm • Temperature characteristics:B to X5R • Capacitance:270000pF to 470000pF
GRM43RB11H334KA01	GRM155R61H334KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):2.00mm to 0.60mm • Temperature characteristics:B to X5R
GRM43RB11H334MA01	GRM155R61H334ME01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):2.00mm to 0.60mm • Temperature characteristics:B to X5R
GRM43RB11H394KA01	GRM155R61H474KE11	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):2.00mm to 0.60mm • Temperature characteristics:B to X5R • Capacitance:390000pF to 470000pF
GRM43RB11H474KA01	GRM155R61H474KE11	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):2.00mm to 0.60mm • Temperature characteristics:B to X5R
GRM43RB11H474KA01	GRM155R61H474KE11	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):2.00mm to 0.60mm • Temperature characteristics:B to X5R
GRM43RB11H474KA22	GRM155R61H474KE11	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):2.00mm to 0.60mm • Temperature characteristics:B to X5R
GRM43RB11H474MA01	GRM155R61H474ME11	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):2.00mm to 0.60mm • Temperature characteristics:B to X5R
GRM43RB11H564KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:560000pF to 1.0uF
GRM43RB11H684KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:680000pF to 1.0uF
GRM43RB11H684MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:680000pF to 1.0uF • Capacitance Tolerance:+20% to +10%
GRM43EB31H475KA88	GRM21BR61H475KE51	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.40mm • Temperature characteristics:B to X5R
GRM43EB31H475MA88	GRM21BR61H475ME51	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.40mm • Temperature characteristics:B to X5R
GRM43XC72A104KW05	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.70mm to 0.90mm • Temperature characteristics:X7S to X7R
GRM43ER11E475KA01	GRM31CR71H475KA12	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 3216M(1206inch) • T size(Max):2.70mm to 1.80mm • Temperature characteristics:R to X7R • Rated Voltage:25V to 50V
GRM43ER11E475MA01	GRM31CR71H475MA12	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 3216M(1206inch) • T size(Max):2.70mm to 1.80mm • Temperature characteristics:R to X7R • Rated Voltage:25V to 50V
GRM43MR11H333KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:33000pF to 47000pF
GRM43MR11H333MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:33000pF to 47000pF
GRM43MR11H393KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:39000pF to 47000pF

GRM43MR11H473KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R
GRM43MR11H473MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R
GRM43MR11H563KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:56000pF to 100000pF
GRM43MR11H683KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:68000pF to 100000pF
GRM43MR11H683MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:68000pF to 100000pF
GRM43MR11H823KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:82000pF to 100000pF
GRM43MR11H104KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R
GRM43MR11H104MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R
GRM43MR11H124KA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.87mm • Temperature characteristics:R to X7R • Capacitance:120000pF to 220000pF
GRM43MR11H124MA01	GRM188R71H224MAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.87mm • Temperature characteristics:R to X7R • Capacitance:120000pF to 220000pF
GRM43NR11H154KA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R • Capacitance:150000pF to 220000pF
GRM43NR11H154MA01	GRM188R71H224MAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R • Capacitance:150000pF to 220000pF
GRM43NR11H184KA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R • Capacitance:180000pF to 220000pF
GRM43RR11H224KA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 0.87mm • Temperature characteristics:R to X7R
GRM43RR11H224MA01	GRM188R71H224MAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 0.87mm • Temperature characteristics:R to X7R
GRM43RR11H274KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:270000pF to 1.0uF
GRM43RR11H334KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:330000pF to 1.0uF
GRM43RR11H334MA01	GRM188D71H105ME01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:330000pF to 1.0uF
GRM43RR11H394KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:390000pF to 1.0uF

GRM43RR11H474KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:470000pF to 1.0uF
GRM43RR11H474MA01	GRM188D71H105ME01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:470000pF to 1.0uF
GRM43RR11H564KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:560000pF to 1.0uF
GRM43RR11H684KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:680000pF to 1.0uF
GRM43RR11H684MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:680000pF to 1.0uF • Capacitance Tolerance:±20% to ±10%
GRM43DR11H155KA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.20mm to 1.45mm • Temperature characteristics:R to X7T • Capacitance:1.5uF to 2.2uF
GRM43DR11H155MA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.20mm to 1.45mm • Temperature characteristics:R to X7T • Capacitance:1.5uF to 2.2uF • Capacitance Tolerance:±20% to ±10%
GRM43ER11H225KA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.45mm • Temperature characteristics:R to X7T
GRM43ER11H225KA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.45mm • Temperature characteristics:R to X7T
GRM43ER11H225MA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.45mm • Temperature characteristics:R to X7T • Capacitance Tolerance:±20% to ±10%
GRM43ER61C226KE01	GRM219R61C226ME15	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.00mm • Capacitance Tolerance:±10% to ±20%
GRM43ER61C226ME01	GRM219R61C226ME15	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.00mm
GRM43DR61E106KA12	GRM188R61E106KA73	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.20mm to 1.00mm
GRM43DR61E106KA12	GRM188R61E106KA73	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.20mm to 1.00mm
GRM43DR61E106KA12	GRM188R61E106KA73	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.20mm to 1.00mm
GRM43DR61E106MA12	GRM188R61E106MA73	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.20mm to 1.00mm
GRM43ER61H475KA88	GRM21BR61H475KE51	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.40mm
GRM43ER61H475MA88	GRM21BR61H475ME51	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.40mm
GRM43DR62A334KW01	GRM188D72A105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X5R to X7T • Capacitance:330000pF to 1.0uF

GRM43DR62A334KW01	GRM188D72A105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X5R to X7T • Capacitance:330000pF to 1.0uF
GRM43DR62A474KW01	GRM188D72A105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X5R to X7T • Capacitance:470000pF to 1.0uF
GRM43DR62A474KW01	GRM188D72A105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X5R to X7T • Capacitance:470000pF to 1.0uF
GRM43ER71E475KA01	GRM31CR71H475KA12	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 3216M(1206inch) • T size(Max):2.70mm to 1.80mm • Rated Voltage:25V to 50V
GRM43ER71E475MA01	GRM31CR71H475MA12	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 3216M(1206inch) • T size(Max):2.70mm to 1.80mm • Rated Voltage:25V to 50V
GRM43MR71H623JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:62000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM43MR71H913JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:91000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM43MR71H333JA26	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:33000pF to 47000pF • Capacitance Tolerance:±5% to ±10%
GRM43MR71H363JA26	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:36000pF to 47000pF • Capacitance Tolerance:±5% to ±10%
GRM43MR71H393JA26	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:39000pF to 47000pF • Capacitance Tolerance:±5% to ±10%
GRM43MR71H433JA26	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:43000pF to 47000pF • Capacitance Tolerance:±5% to ±10%
GRM43MR71H473JA26	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance Tolerance:±5% to ±10%
GRM43MR71H473KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm
GRM43MR71H513JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:51000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM43MR71H563JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:56000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM43MR71H683JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:68000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM43MR71H753JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:75000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM43MR71H823JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:82000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM43MR71H104JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance Tolerance:±5% to ±10%

GRM43MR71H104JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance Tolerance:±5% to ±10%
GRM43MR71H104KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm
GRM43MR71H114JA26	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.87mm • Capacitance:110000pF to 220000pF • Capacitance Tolerance:±5% to ±10%
GRM43MR71H124JA26	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.87mm • Capacitance:120000pF to 220000pF • Capacitance Tolerance:±5% to ±10%
GRM43NR71H134JA26	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Capacitance:130000pF to 220000pF • Capacitance Tolerance:±5% to ±10%
GRM43NR71H154JA26	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Capacitance:150000pF to 220000pF • Capacitance Tolerance:±5% to ±10%
GRM43NR71H154KA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Capacitance:150000pF to 220000pF
GRM43NR71H164JA26	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Capacitance:160000pF to 220000pF • Capacitance Tolerance:±5% to ±10%
GRM43NR71H184JA26	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Capacitance:180000pF to 220000pF • Capacitance Tolerance:±5% to ±10%
GRM43RR71H204JA26	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 0.87mm • Capacitance:200000pF to 220000pF • Capacitance Tolerance:±5% to ±10%
GRM43RR71H224JA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 0.87mm • Capacitance Tolerance:±5% to ±10%
GRM43RR71H224JA26	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 0.87mm • Capacitance Tolerance:±5% to ±10%
GRM43RR71H224KA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 0.87mm
GRM43RR71H224MA01	GRM188R71H224MAC4	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 0.87mm
GRM43RR71H244JA26	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:240000pF to 1.0uF
GRM43RR71H274JA26	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:270000pF to 1.0uF • Capacitance Tolerance:±5% to ±10%
GRM43RR71H274KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:270000pF to 1.0uF
GRM43RR71H274MA01	GRM188D71H105ME01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:270000pF to 1.0uF
GRM43RR71H304JA26	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:300000pF to 1.0uF • Capacitance Tolerance:±5% to ±10%

GRM43DR71H155KA36	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.20mm to 1.45mm • Temperature characteristics:X7R to X7T • Capacitance:1.5uF to 2.2uF
GRM43DR71H155MA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.20mm to 1.45mm • Temperature characteristics:X7R to X7T • Capacitance:1.5uF to 2.2uF • Capacitance Tolerance:±20% to ±10%
GRM43ER71H225KA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.45mm • Temperature characteristics:X7R to X7T
GRM43ER71H225KA36	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.45mm • Temperature characteristics:X7R to X7T
GRM43ER71H225MA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.45mm • Temperature characteristics:X7R to X7T • Capacitance Tolerance:±20% to ±10%
GRM43MR72A333KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.90mm • Capacitance:33000pF to 100000pF
GRM43MR72A333MA01	GRM188R72A104MA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.90mm • Capacitance:33000pF to 100000pF
GRM43MR72A393KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.90mm • Capacitance:39000pF to 100000pF
GRM43MR72A473KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.90mm • Capacitance:47000pF to 100000pF
GRM43MR72A473MA01	GRM188R72A104MA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.90mm • Capacitance:47000pF to 100000pF
GRM43MR72A563KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.90mm • Capacitance:56000pF to 100000pF
GRM43MR72A683KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.90mm • Capacitance:68000pF to 100000pF
GRM43MR72A683MA01	GRM188R72A104MA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.90mm • Capacitance:68000pF to 100000pF
GRM43MR72A823KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.90mm • Capacitance:82000pF to 100000pF
GRM43NR72A104JA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.90mm • Capacitance Tolerance:±5% to ±10%
GRM43NR72A104KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.90mm
GRM43NR72A104KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.90mm
GRM43NR72A104KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.90mm
GRM43NR72A104KA26	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.90mm

GRM43DR72A474KW01	GRM188D72A105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:470000pF to 1.0uF
GRM43DR72A474MA01	GRM188D72A105KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 1608M(0603inch) • T size(Max):2.20mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:470000pF to 1.0uF • Capacitance Tolerance:±20% to ±10%
GRM43DR72A155KA01	GRM21BD72A225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.20mm to 1.45mm • Temperature characteristics:X7R to X7T • Capacitance:1.5uF to 2.2uF
GRM43DR72A155KA36	GRM21BD72A225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.20mm to 1.45mm • Temperature characteristics:X7R to X7T • Capacitance:1.5uF to 2.2uF
GRM43DR72A155MA01	GRM21BD72A225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.20mm to 1.45mm • Temperature characteristics:X7R to X7T • Capacitance:1.5uF to 2.2uF • Capacitance Tolerance:±20% to ±10%
GRM43ER72A225KA01	GRM21BD72A225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.45mm • Temperature characteristics:X7R to X7T
GRM43ER72A225KA36	GRM21BD72A225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.45mm • Temperature characteristics:X7R to X7T
GRM43ER72A225MA01	GRM21BD72A225KE01	<ul style="list-style-type: none"> • LW size:4532M(1812inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.45mm • Temperature characteristics:X7R to X7T • Capacitance Tolerance:±20% to ±10%
GRM55DB11E106KA01	GRM188R61E106KA73	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.10mm to 1.00mm • Temperature characteristics:B to X5R
GRM55DB11E106MA01	GRM188R61E106MA73	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.10mm to 1.00mm • Temperature characteristics:B to X5R
GRM55EB11E156KA01	GRM21BR61E226ME44	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.45mm • Temperature characteristics:B to X5R • Capacitance:15uF to 22uF • Capacitance Tolerance:±10% to ±20%
GRM55EB11E156MA01	GRM21BR61E226ME44	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.45mm • Temperature characteristics:B to X5R • Capacitance:15uF to 22uF
GRM55MB11H224KA01	GRM155R61H224KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R
GRM55MB11H224MA01	GRM155R61H224ME01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R
GRM55MB11H274KA01	GRM155R61H474KE11	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.60mm • Temperature characteristics:B to X5R • Capacitance:270000pF to 470000pF
GRM55MB11H334KA01	GRM155R61H334KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.60mm • Temperature characteristics:B to X5R
GRM55MB11H334MA01	GRM155R61H334ME01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.60mm • Temperature characteristics:B to X5R
GRM55NB11H394KA01	GRM155R61H474KE11	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1005M(0402inch) • T size(Max):1.50mm to 0.60mm • Temperature characteristics:B to X5R • Capacitance:390000pF to 470000pF
GRM55RB11H474KA01	GRM155R61H474KE11	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1005M(0402inch) • T size(Max):2.00mm to 0.60mm • Temperature characteristics:B to X5R

GRM55RB11H474MA01	GRM155R61H474ME11	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1005M(0402inch) • T size(Max):2.00mm to 0.60mm • Temperature characteristics:B to X5R
GRM55RB11H564KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:560000pF to 1.0uF
GRM55RB11H684KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:680000pF to 1.0uF
GRM55RB11H684MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:680000pF to 1.0uF • Capacitance Tolerance:±20% to ±10%
GRM55RB11H824KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:820000pF to 1.0uF
GRM55RB11H105JA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance Tolerance:±5% to ±10%
GRM55RB11H105KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X7T
GRM55RB11H105MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance Tolerance:±20% to ±10%
GRM55RB11H125JA01	GRM188R61H225KE11	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X5R • Capacitance:1.2uF to 2.2uF • Capacitance Tolerance:±5% to ±10%
GRM55RB11H125KA01	GRM188R61H225KE11	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X5R • Capacitance:1.2uF to 2.2uF
GRM55RB11H125MA01	GRM188R61H225ME11	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X5R • Capacitance:1.2uF to 2.2uF
GRM55RB11H155JA01	GRM188R61H225KE11	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X5R • Capacitance:1.5uF to 2.2uF • Capacitance Tolerance:±5% to ±10%
GRM55RB11H155KA01	GRM188R61H225KE11	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X5R • Capacitance:1.5uF to 2.2uF
GRM55RB11H155MA01	GRM188R61H225ME11	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:B to X5R • Capacitance:1.5uF to 2.2uF
GRM55EB11H475KA01	GRM21BR61H475KE51	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inchi) • T size(Max):2.70mm to 1.40mm • Temperature characteristics:B to X5R
GRM55EB11H475MA01	GRM21BR61H475ME51	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inchi) • T size(Max):2.70mm to 1.40mm • Temperature characteristics:B to X5R
GRM55DB31H106KA87	GRM32ER71H106KA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3225M(1210inch) • T size(Max):2.20mm to 2.70mm • Temperature characteristics:B to X7R
GRM55DB31H106KA87	GRM32ER71H106KA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3225M(1210inch) • T size(Max):2.10mm to 2.70mm • Temperature characteristics:B to X7R
GRM55DB31H106MA87	GRM32ER71H106MA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3225M(1210inch) • T size(Max):2.10mm to 2.70mm • Temperature characteristics:B to X7R

GRM55DR11E106KA01	GRM31CR71E106KA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3216M(1206inch) • T size(Max):2.10mm to 1.80mm • Temperature characteristics:R to X7R
GRM55DR11E106MA01	GRM31CR71E106MA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3216M(1206inch) • T size(Max):2.10mm to 1.80mm • Temperature characteristics:R to X7R
GRM55ER11E156KA01	GRM32ER71E226KE15	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3225M(1210inch) • Temperature characteristics:R to X7R • Capacitance:15uF to 22uF
GRM55ER11E156MA01	GRM32ER71E226ME15	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3225M(1210inch) • Temperature characteristics:R to X7R • Capacitance:15uF to 22uF
GRM55MR11H224KA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.87mm • Temperature characteristics:R to X7R
GRM55MR11H224MA01	GRM188R71H224MAC4	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.87mm • Temperature characteristics:R to X7R
GRM55MR11H274KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:270000pF to 1.0uF
GRM55MR11H274MA01	GRM188D71H105ME01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:270000pF to 1.0uF
GRM55MR11H334KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:330000pF to 1.0uF
GRM55MR11H334MA01	GRM188D71H105ME01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:330000pF to 1.0uF
GRM55NR11H394KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:390000pF to 1.0uF
GRM55NR11H394MA01	GRM188D71H105ME01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:390000pF to 1.0uF
GRM55RR11H474KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:470000pF to 1.0uF
GRM55RR11H474MA01	GRM188D71H105ME01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:470000pF to 1.0uF
GRM55RR11H564KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:560000pF to 1.0uF
GRM55RR11H564MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:560000pF to 1.0uF • Capacitance Tolerance:±20% to ±10%
GRM55RR11H684KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:680000pF to 1.0uF
GRM55RR11H684MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:680000pF to 1.0uF • Capacitance Tolerance:±20% to ±10%
GRM55RR11H824KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:820000pF to 1.0uF

GRM55RR11H105JA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance Tolerance:±5% to ±10%
GRM55RR11H105KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T
GRM55RR11H105MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance Tolerance:±20% to ±10%
GRM55RR11H125JA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.00mm to 1.45mm • Temperature characteristics:R to X7T • Capacitance:1.2uF to 2.2uF • Capacitance Tolerance:±5% to ±10%
GRM55RR11H125KA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.00mm to 1.45mm • Temperature characteristics:R to X7T • Capacitance:1.2uF to 2.2uF
GRM55RR11H125MA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.00mm to 1.45mm • Temperature characteristics:R to X7T • Capacitance:1.2uF to 2.2uF
GRM55RR11H125MA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.00mm to 1.45mm • Temperature characteristics:R to X7T • Capacitance:1.2uF to 2.2uF
GRM55RR11H155JA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.00mm to 1.45mm • Temperature characteristics:R to X7T • Capacitance:1.5uF to 2.2uF • Capacitance Tolerance:±5% to ±10%
GRM55RR11H155KA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.00mm to 1.45mm • Temperature characteristics:R to X7T • Capacitance:1.5uF to 2.2uF
GRM55RR11H155MA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.00mm to 1.45mm • Temperature characteristics:R to X7T • Capacitance:1.5uF to 2.2uF • Capacitance Tolerance:±20% to ±10%
GRM55DR11H335KA01	GRM31CR71H475KA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3216M(1206inch) • T size(Max):2.20mm to 1.80mm • Temperature characteristics:R to X7R • Capacitance:3.3uF to 4.7uF
GRM55DR11H335MA01	GRM31CR71H475MA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3216M(1206inch) • T size(Max):2.20mm to 1.80mm • Temperature characteristics:R to X7R • Capacitance:3.3uF to 4.7uF
GRM55ER11H475KA01	GRM31CR71H475KA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3216M(1206inch) • T size(Max):2.70mm to 1.80mm • Temperature characteristics:R to X7R
GRM55ER11H475MA01	GRM31CR71H475MA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3216M(1206inch) • T size(Max):2.70mm to 1.80mm • Temperature characteristics:R to X7R
GRM55DR61H335KA01	GRM21BR61H475KE51	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.20mm to 1.40mm • Capacitance:3.3uF to 4.7uF
GRM55DR61H335MA01	GRM21BR61H475ME51	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.20mm to 1.40mm • Capacitance:3.3uF to 4.7uF
GRM55ER61H475KA01	GRM21BR61H475KE51	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.40mm
GRM55ER61H475MA01	GRM21BR61H475ME51	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.70mm to 1.40mm
GRM55DR61H106KA88	GRM32ER71H106KA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3225M(1210inch) • T size(Max):2.20mm to 2.70mm • Temperature characteristics:X5R to X7R

GRM55DR61H106MA88	GRM32ER71H106MA12	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 3225M(1210inch) ·T size(Max):2.10mm to 2.70mm · Temperature characteristics:X5R to X7R
GRM55ER61J475KA12	GRM31CC72A475KE11	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 3216M(1206inch) ·T size(Max):2.70mm to 1.90mm · Temperature characteristics:X5R to X7S ·Rated Voltage:63V to 100V
GRM55ER61J475MA12	GRM31CC72A475ME11	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 3216M(1206inch) ·T size(Max):2.70mm to 1.90mm · Temperature characteristics:X5R to X7S ·Rated Voltage:63V to 100V
GRM55DR62A105KW01	GRM188D72A105KE01	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 1608M(0603inch) ·T size(Max):2.00mm to 1.00mm · Temperature characteristics:X5R to X7T
GRM55DR62A105KW01	GRM188D72A105KE01	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 1608M(0603inch) ·T size(Max):2.00mm to 1.00mm · Temperature characteristics:X5R to X7T
GRM55DR71E106KA01	GRM31CR71E106KA12	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 3216M(1206inch) ·T size(Max):2.10mm to 1.80mm
GRM55DR71E106KA36	GRM31CR71E106KA12	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 3216M(1206inch) ·T size(Max):2.10mm to 1.80mm
GRM55DR71E106MA01	GRM31CR71E106MA12	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 3216M(1206inch) ·T size(Max):2.10mm to 1.80mm
GRM55ER71E156KA01	GRM32ER71E226KE15	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 3225M(1210inch) ·Capacitance:15uF to 22uF
GRM55ER71E156MA01	GRM32ER71E226ME15	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 3225M(1210inch) ·Capacitance:15uF to 22uF
GRM55MR71H334KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 1608M(0603inch) ·T size(Max):1.25mm to 1.00mm · Temperature characteristics:X7R to X7T ·Capacitance:330000pF to 1.0uF
GRM55RR71H474KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 1608M(0603inch) ·T size(Max):2.00mm to 1.00mm · Temperature characteristics:X7R to X7T ·Capacitance:470000pF to 1.0uF
GRM55RR71H564KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 1608M(0603inch) ·T size(Max):2.00mm to 1.00mm · Temperature characteristics:X7R to X7T ·Capacitance:560000pF to 1.0uF
GRM55RR71H564MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 1608M(0603inch) ·T size(Max):2.00mm to 1.00mm · Temperature characteristics:X7R to X7T ·Capacitance:560000pF to 1.0uF · Capacitance Tolerance:+20% to +10%
GRM55RR71H624KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 1608M(0603inch) ·T size(Max):2.00mm to 1.00mm · Temperature characteristics:X7R to X7T ·Capacitance:620000pF to 1.0uF
GRM55RR71H624MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 1608M(0603inch) ·T size(Max):2.00mm to 1.00mm · Temperature characteristics:X7R to X7T ·Capacitance:620000pF to 1.0uF · Capacitance Tolerance:+20% to +10%
GRM55RR71H684KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 1608M(0603inch) ·T size(Max):2.00mm to 1.00mm · Temperature characteristics:X7R to X7T ·Capacitance:680000pF to 1.0uF
GRM55RR71H684MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 1608M(0603inch) ·T size(Max):2.00mm to 1.00mm · Temperature characteristics:X7R to X7T ·Capacitance:680000pF to 1.0uF · Capacitance Tolerance:+20% to +10%
GRM55RR71H754KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> ·LW size:5750M(2220inch) to 1608M(0603inch) ·T size(Max):2.00mm to 1.00mm · Temperature characteristics:X7R to X7T ·Capacitance:750000pF to 1.0uF

GRM55RR71H754MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:750000pF to 1.0uF • Capacitance Tolerance:+20% to +10%
GRM55RR71H824KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:820000pF to 1.0uF • Capacitance Tolerance:+20% to +10%
GRM55RR71H824MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:820000pF to 1.0uF • Capacitance Tolerance:+20% to +10%
GRM55RR71H914KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:910000pF to 1.0uF • Capacitance Tolerance:+20% to +10%
GRM55RR71H914MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:910000pF to 1.0uF • Capacitance Tolerance:+20% to +10%
GRM55RR71H105JA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance Tolerance:±5% to ±10%
GRM55RR71H105KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T
GRM55RR71H105KA26	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T
GRM55RR71H105MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance Tolerance:±20% to ±10%
GRM55RR71H125JA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.00mm to 1.45mm • Temperature characteristics:X7R to X7T • Capacitance:1.2uF to 2.2uF • Capacitance Tolerance:+5% to +10%
GRM55RR71H125KA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.00mm to 1.45mm • Temperature characteristics:X7R to X7T • Capacitance:1.2uF to 2.2uF • Capacitance Tolerance:+5% to +10%
GRM55RR71H125MA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.00mm to 1.45mm • Temperature characteristics:X7R to X7T • Capacitance:1.2uF to 2.2uF • Capacitance Tolerance:+20% to +10%
GRM55RR71H155JA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.00mm to 1.45mm • Temperature characteristics:X7R to X7T • Capacitance:1.5uF to 2.2uF • Capacitance Tolerance:+5% to +10%
GRM55RR71H155KA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.00mm to 1.45mm • Temperature characteristics:X7R to X7T • Capacitance:1.5uF to 2.2uF • Capacitance Tolerance:+5% to +10%
GRM55RR71H155MA01	GRM21BD71H225KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 2012M(0805inch) • T size(Max):2.00mm to 1.45mm • Temperature characteristics:X7R to X7T • Capacitance:1.5uF to 2.2uF • Capacitance Tolerance:+20% to +10%
GRM55DR71H335KA01	GRM31CR71H475KA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3216M(1206inch) • T size(Max):2.20mm to 1.80mm • Capacitance:3.3uF to 4.7uF
GRM55DR71H335MA01	GRM31CR71H475MA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3216M(1206inch) • T size(Max):2.20mm to 1.80mm • Capacitance:3.3uF to 4.7uF
GRM55ER71H475KA01	GRM31CR71H475KA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3216M(1206inch) • T size(Max):2.70mm to 1.80mm
GRM55ER71H475MA01	GRM31CR71H475MA12	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3216M(1206inch) • T size(Max):2.70mm to 1.80mm

GRM55ER71J475KA12	GRM31CC72A475KE11	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3216M(1206inch) • T size(Max):2.70mm to 1.90mm • Temperature characteristics:X7R to X7S • Rated Voltage:63V to 100V
GRM55ER71J475MA12	GRM31CC72A475KE11	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 3216M(1206inch) • T size(Max):2.70mm to 1.90mm • Temperature characteristics:X7R to X7S • Rated Voltage:63V to 100V • Capacitance Tolerance:±20% to ±10%
GRM55NR72A224KA01	GRM188D72A105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:220000pF to 1.0uF
GRM55NR72A224MA01	GRM188D72A105ME01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:220000pF to 1.0uF
GRM55NR72A274KA01	GRM188D72A105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:270000pF to 1.0uF
GRM55RR72A334KA01	GRM188D72A105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:330000pF to 1.0uF
GRM55RR72A334MA01	GRM188D72A105ME01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:330000pF to 1.0uF
GRM55RR72A364KA01	GRM188D72A105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:360000pF to 1.0uF
GRM55RR72A364MA01	GRM188D72A105ME01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:360000pF to 1.0uF
GRM55RR72A394KA01	GRM188D72A105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:390000pF to 1.0uF
GRM55RR72A394MA01	GRM188D72A105ME01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:390000pF to 1.0uF
GRM55RR72A434KA01	GRM188D72A105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:430000pF to 1.0uF
GRM55RR72A434MA01	GRM188D72A105ME01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:430000pF to 1.0uF
GRM55RR72A474KA01	GRM188D72A105KE01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:470000pF to 1.0uF
GRM55RR72A474MA01	GRM188D72A105ME01	<ul style="list-style-type: none"> • LW size:5750M(2220inch) to 1608M(0603inch) • T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:470000pF to 1.0uF

GRM55DR72A824KA01	GRM188D72A105KE01	<ul style="list-style-type: none"> •LW size:5750M(2220inch) to 1608M(0603inch) •T size(Max):2.20mm to 1.00mm • Temperature characteristics:X7R to X7T •Capacitance:820000pF to 1.0uF
GRM55DR72A105KA01	GRM188D72A105KE01	<ul style="list-style-type: none"> •LW size:5750M(2220inch) to 1608M(0603inch) •T size(Max):2.20mm to 1.00mm • Temperature characteristics:X7R to X7T
GRM55DR72A105KA36	GRM188D72A105KE01	<ul style="list-style-type: none"> •LW size:5750M(2220inch) to 1608M(0603inch) •T size(Max):2.20mm to 1.00mm • Temperature characteristics:X7R to X7T
GRM55DR72A105KW01	GRM188D72A105KE01	<ul style="list-style-type: none"> •LW size:5750M(2220inch) to 1608M(0603inch) •T size(Max):2.00mm to 1.00mm • Temperature characteristics:X7R to X7T
GRM55DR72A105MA01	GRM188D72A105ME01	<ul style="list-style-type: none"> •LW size:5750M(2220inch) to 1608M(0603inch) •T size(Max):2.20mm to 1.00mm • Temperature characteristics:X7R to X7T
GRM55DR72A335KA01	GRM31CC72A475KE11	<ul style="list-style-type: none"> •LW size:5750M(2220inch) to 3216M(1206inch) •T size(Max):2.20mm to 1.90mm • Temperature characteristics:X7R to X7S •Capacitance:3.3uF to 4.7uF
GRM55DR72A335MA01	GRM31CC72A475KE11	<ul style="list-style-type: none"> •LW size:5750M(2220inch) to 3216M(1206inch) •T size(Max):2.20mm to 1.90mm • Temperature characteristics:X7R to X7S •Capacitance:3.3uF to 4.7uF • Capacitance Tolerance:±20% to ±10%
GRM55ER72A475KA01	GRM31CC72A475KE11	<ul style="list-style-type: none"> •LW size:5750M(2220inch) to 3216M(1206inch) •T size(Max):2.70mm to 1.90mm • Temperature characteristics:X7R to X7S
GRM55ER72A475MA01	GRM31CC72A475KE11	<ul style="list-style-type: none"> •LW size:5750M(2220inch) to 3216M(1206inch) •T size(Max):2.70mm to 1.90mm • Temperature characteristics:X7R to X7S • Capacitance Tolerance:±20% to ±10%
GCM32NR11E564KA01	GCM188R71E105KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm • Temperature characteristics:R to X7R •Capacitance:560000pF to 1.0uF
GCM32NR11E564MA01	GCM188R71E105MA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm • Temperature characteristics:R to X7R •Capacitance:560000pF to 1.0uF
GCM32NR11E684KA01	GCM188R71E105KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm • Temperature characteristics:R to X7R •Capacitance:680000pF to 1.0uF
GCM32NR11E684MA01	GCM188R71E105MA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm • Temperature characteristics:R to X7R •Capacitance:680000pF to 1.0uF
GCM329R11H623KA01	GCM155R71H104KE02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:62000pF to 100000pF
GCM329R11H623MA01	GCM155R71H104ME02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:62000pF to 100000pF
GCM32MR11H913KA01	GCM155R71H104KE02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:91000pF to 100000pF
GCM32MR11H913MA01	GCM155R71H104ME02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:91000pF to 100000pF
GCM329R11H103KA01	GCM155R71H103KA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H103MA01	GCM155R71H103MA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R

GCM329R11H113KA01	GCM155R71H223KA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:11000pF to 22000pF
GCM329R11H113MA01	GCM155R71H223MA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:11000pF to 22000pF
GCM329R11H123KA01	GCM155R71H123KA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H123MA01	GCM155R71H123MA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H133KA01	GCM155R71H223KA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:13000pF to 22000pF
GCM329R11H133MA01	GCM155R71H223MA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:13000pF to 22000pF
GCM329R11H153KA01	GCM155R71H153KA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H153MA01	GCM155R71H153MA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H163KA01	GCM155R71H223KA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:16000pF to 22000pF
GCM329R11H163MA01	GCM155R71H223MA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:16000pF to 22000pF
GCM329R11H183KA01	GCM155R71H183KA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H183MA01	GCM155R71H183MA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H203KA01	GCM155R71H223KA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:20000pF to 22000pF
GCM329R11H203MA01	GCM155R71H223MA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:20000pF to 22000pF
GCM329R11H223KA01	GCM155R71H223KA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H223MA01	GCM155R71H223MA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H243KA01	GCM155R71H473KE02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:24000pF to 47000pF
GCM329R11H243MA01	GCM155R71H473ME02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:24000pF to 47000pF
GCM329R11H273KA01	GCM219R72A273KA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.00mm to 0.95mm • Temperature characteristics:R to X7R •Rated Voltage:50V to 100V

GCM329R11H273MA01	GCM219R72A273MA37	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.00mm to 0.95mm • Temperature characteristics:R to X7R • Rated Voltage:50V to 100V
GCM329R11H303KA01	GCM155R71H473KE02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:30000pF to 47000pF
GCM329R11H303MA01	GCM155R71H473ME02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:30000pF to 47000pF
GCM329R11H333KA01	GCM155R71H333KE02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H333MA01	GCM155R71H333ME02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H363KA01	GCM155R71H473KE02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:36000pF to 47000pF
GCM329R11H363MA01	GCM155R71H473ME02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:36000pF to 47000pF
GCM329R11H393KA01	GCM219R72A393KA37	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.00mm to 0.95mm • Temperature characteristics:R to X7R • Rated Voltage:50V to 100V
GCM329R11H393MA01	GCM219R72A393MA37	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.00mm to 0.95mm • Temperature characteristics:R to X7R • Rated Voltage:50V to 100V
GCM329R11H433KA01	GCM155R71H473KE02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:43000pF to 47000pF
GCM329R11H433MA01	GCM155R71H473ME02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:43000pF to 47000pF
GCM329R11H473KA01	GCM155R71H473KE02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H473MA01	GCM155R71H473ME02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H513KA01	GCM155R71H104KE02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:51000pF to 100000pF
GCM329R11H513MA01	GCM155R71H104ME02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:51000pF to 100000pF
GCM329R11H563KA01	GCM21BR72A563KA37	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.00mm to 1.35mm • Temperature characteristics:R to X7R • Rated Voltage:50V to 100V
GCM329R11H563MA01	GCM21BR72A563MA37	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.00mm to 1.35mm • Temperature characteristics:R to X7R • Rated Voltage:50V to 100V
GCM329R11H683KA01	GCM155R71H683KE02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GCM329R11H683MA01	GCM155R71H683ME02	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R

GCM32MR11H753KA01	GCM155R71H104KE02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:75000pF to 100000pF
GCM32MR11H753MA01	GCM155R71H104ME02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:75000pF to 100000pF
GCM32MR11H823KA01	GCM21BR72A823KA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.25mm to 1.35mm • Temperature characteristics:R to X7R •Rated Voltage:50V to 100V
GCM32MR11H823MA01	GCM21BR72A823MA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.25mm to 1.35mm • Temperature characteristics:R to X7R •Rated Voltage:50V to 100V
GCM32MR11H104KA01	GCM155R71H104KE02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R
GCM32MR11H104MA01	GCM155R71H104ME02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R
GCM32MR11H114KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.25mm to 0.87mm • Temperature characteristics:R to X7R •Capacitance:110000pF to 220000pF
GCM32MR11H114MA01	GCM188R71H224MA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.25mm to 0.87mm • Temperature characteristics:R to X7R •Capacitance:110000pF to 220000pF
GCM32NR11H124KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R •Capacitance:120000pF to 220000pF
GCM32NR11H124MA01	GCM188R71H224MA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R •Capacitance:120000pF to 220000pF
GCM32NR11H134KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R •Capacitance:130000pF to 220000pF
GCM32NR11H134MA01	GCM188R71H224MA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R •Capacitance:130000pF to 220000pF
GCM32NR11H154KA01	GCM188R71H154KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R
GCM32NR11H154MA01	GCM188R71H154MA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R
GCM32NR11H164KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R •Capacitance:160000pF to 220000pF
GCM32NR11H164MA01	GCM188R71H224MA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R •Capacitance:160000pF to 220000pF
GCM32NR11H184KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R •Capacitance:180000pF to 220000pF
GCM32NR11H184MA01	GCM188R71H224MA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R •Capacitance:180000pF to 220000pF
GCM32NR11H204KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R •Capacitance:200000pF to 220000pF

GCM32NR11H204MA01	GCM188R71H224MA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R •Capacitance:200000pF to 220000pF
GCM32NR11H224KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R
GCM32NR11H224MA01	GCM188R71H224KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±20% to ±10%
GCM32MR71E474KA02	GCM188R71E474KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.25mm to 0.90mm
GCM32NR71E564KA01	GCM188R71E105KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:560000pF to 1.0uF
GCM32NR71E564MA01	GCM188R71E105MA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:560000pF to 1.0uF
GCM32NR71E684KA01	GCM188R71E105KA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:680000pF to 1.0uF
GCM32NR71E684MA01	GCM188R71E105MA64	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:680000pF to 1.0uF
GCM329R71H623KA01	GCM155R71H104KE02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:62000pF to 100000pF
GCM329R71H623MA01	GCM155R71H104ME02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:62000pF to 100000pF
GCM32MR71H913KA01	GCM155R71H104KE02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.25mm to 0.55mm •Capacitance:91000pF to 100000pF
GCM32MR71H913MA01	GCM155R71H104ME02	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.25mm to 0.55mm •Capacitance:91000pF to 100000pF
GCM329R71H103KA01	GCM155R71H103KA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm
GCM329R71H103MA01	GCM155R71H103MA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm
GCM329R71H113KA01	GCM155R71H223KA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:11000pF to 22000pF
GCM329R71H113MA01	GCM155R71H223MA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:11000pF to 22000pF
GCM329R71H123KA01	GCM155R71H123KA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm
GCM329R71H123MA01	GCM155R71H123MA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm
GCM329R71H133KA01	GCM155R71H223KA55	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:13000pF to 22000pF

GCM329R71H133MA01	GCM155R71H223MA55	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:13000pF to 22000pF
GCM329R71H153KA01	GCM155R71H153KA55	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GCM329R71H153MA01	GCM155R71H153MA55	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GCM329R71H163KA01	GCM155R71H223KA55	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:16000pF to 22000pF
GCM329R71H163MA01	GCM155R71H223MA55	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:16000pF to 22000pF
GCM329R71H183KA01	GCM155R71H183KA55	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GCM329R71H183MA01	GCM155R71H183MA55	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GCM329R71H203KA01	GCM155R71H223KA55	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:20000pF to 22000pF
GCM329R71H203MA01	GCM155R71H223MA55	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:20000pF to 22000pF
GCM329R71H223KA01	GCM155R71H223KA55	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GCM329R71H223MA01	GCM155R71H223MA55	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GCM329R71H243KA01	GCM155R71H473KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:24000pF to 47000pF
GCM329R71H243MA01	GCM155R71H473ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:24000pF to 47000pF
GCM329R71H273KA01	GCM155R71H473KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:27000pF to 47000pF
GCM329R71H273MA01	GCM155R71H473ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:27000pF to 47000pF
GCM329R71H303KA01	GCM155R71H473KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:30000pF to 47000pF
GCM329R71H303MA01	GCM155R71H473ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:30000pF to 47000pF
GCM329R71H333KA01	GCM155R71H333KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GCM329R71H333MA01	GCM155R71H333ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm

GCM329R71H363KA01	GCM155R71H473KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:36000pF to 47000pF
GCM329R71H363MA01	GCM155R71H473ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:36000pF to 47000pF
GCM329R71H393KA01	GCM155R71H473KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:39000pF to 47000pF
GCM329R71H393MA01	GCM155R71H473ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:39000pF to 47000pF
GCM329R71H433KA01	GCM155R71H473KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:43000pF to 47000pF
GCM329R71H433MA01	GCM155R71H473ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:43000pF to 47000pF
GCM329R71H473KA01	GCM155R71H473KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GCM329R71H473MA01	GCM155R71H473ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GCM329R71H513KA01	GCM155R71H104KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:51000pF to 100000pF
GCM329R71H513MA01	GCM155R71H104ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:51000pF to 100000pF
GCM329R71H563KA01	GCM155R71H104KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:56000pF to 100000pF
GCM329R71H563MA01	GCM155R71H104ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:56000pF to 100000pF
GCM329R71H683KA01	GCM155R71H683KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GCM329R71H683MA01	GCM155R71H683ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GCM32MR71H753KA01	GCM155R71H104KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.25mm to 0.55mm ·Capacitance:75000pF to 100000pF
GCM32MR71H753MA01	GCM155R71H104ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.25mm to 0.55mm ·Capacitance:75000pF to 100000pF
GCM32MR71H823KA01	GCM155R71H104KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.25mm to 0.55mm ·Capacitance:82000pF to 100000pF
GCM32MR71H823MA01	GCM155R71H104ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.25mm to 0.55mm ·Capacitance:82000pF to 100000pF
GCM32MR71H104KA01	GCM155R71H104KE02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.25mm to 0.55mm

GCM32MR71H104MA01	GCM155R71H104ME02	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.25mm to 0.55mm
GCM32MR71H114KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.25mm to 0.87mm ·Capacitance:110000pF to 220000pF
GCM32MR71H114MA01	GCM188R71H224MA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.25mm to 0.87mm ·Capacitance:110000pF to 220000pF
GCM32NR71H124KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm ·Capacitance:120000pF to 220000pF
GCM32NR71H124MA01	GCM188R71H224MA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm ·Capacitance:120000pF to 220000pF
GCM32NR71H134KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm ·Capacitance:130000pF to 220000pF
GCM32NR71H134MA01	GCM188R71H224MA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm ·Capacitance:130000pF to 220000pF
GCM32NR71H154KA01	GCM188R71H154KA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm
GCM32NR71H154MA01	GCM188R71H154MA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm
GCM32NR71H164KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm ·Capacitance:160000pF to 220000pF
GCM32NR71H164MA01	GCM188R71H224MA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm ·Capacitance:160000pF to 220000pF
GCM32NR71H184KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm ·Capacitance:180000pF to 220000pF
GCM32NR71H184MA01	GCM188R71H224MA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm ·Capacitance:180000pF to 220000pF
GCM32NR71H204KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm ·Capacitance:200000pF to 220000pF
GCM32NR71H204MA01	GCM188R71H224MA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm ·Capacitance:200000pF to 220000pF
GCM32NR71H224KA01	GCM188R71H224KA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm
GCM32NR71H224MA01	GCM188R71H224MA64	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.87mm
GCM32NR72A623KA01	GCM21BR72A104KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.50mm to 1.35mm ·Capacitance:62000pF to 100000pF

GCM32NR72A623MA01	GCM21BR72A104MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.50mm to 1.35mm ·Capacitance:62000pF to 100000pF
GCM32NR72A913KA01	GCM21BR72A104KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.50mm to 1.35mm ·Capacitance:91000pF to 100000pF
GCM32NR72A913MA01	GCM21BR72A104MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.50mm to 1.35mm ·Capacitance:91000pF to 100000pF
GCM329R72A103KA01	GCM188R72A103KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm
GCM329R72A103MA01	GCM188R72A103MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm
GCM329R72A113KA01	GCM188R72A223KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm ·Capacitance:11000pF to 22000pF
GCM329R72A113MA01	GCM188R72A223MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm ·Capacitance:11000pF to 22000pF
GCM329R72A123KA01	GCM188R72A123KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm
GCM329R72A123MA01	GCM188R72A123MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm
GCM329R72A133KA01	GCM188R72A223KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm ·Capacitance:13000pF to 22000pF
GCM329R72A133MA01	GCM188R72A223MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm ·Capacitance:13000pF to 22000pF
GCM329R72A153KA01	GCM188R72A153KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm
GCM329R72A153MA01	GCM188R72A153MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm
GCM329R72A163KA01	GCM188R72A223KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm ·Capacitance:16000pF to 22000pF
GCM329R72A163MA01	GCM188R72A223MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm ·Capacitance:16000pF to 22000pF
GCM329R72A183KA01	GCM188R72A183KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm
GCM329R72A183MA01	GCM188R72A183MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm
GCM329R72A203KA01	GCM188R72A223KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm ·Capacitance:20000pF to 22000pF
GCM329R72A203MA01	GCM188R72A223MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm ·Capacitance:20000pF to 22000pF

GCM329R72A223KA01	GCM188R72A223KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm
GCM329R72A223MA01	GCM188R72A223MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.00mm to 0.87mm
GCM329R72A243KA01	GCM21BR72A473KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.00mm to 1.35mm ·Capacitance:24000pF to 47000pF
GCM329R72A243MA01	GCM21BR72A473MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.00mm to 1.35mm ·Capacitance:24000pF to 47000pF
GCM329R72A273KA01	GCM219R72A273KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.00mm to 0.95mm
GCM329R72A273MA01	GCM219R72A273MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.00mm to 0.95mm
GCM329R72A303KA01	GCM21BR72A473KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.00mm to 1.35mm ·Capacitance:30000pF to 47000pF
GCM329R72A303MA01	GCM21BR72A473MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.00mm to 1.35mm ·Capacitance:30000pF to 47000pF
GCM32MR72A333KA01	GCM219R72A333KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.25mm to 0.95mm
GCM32MR72A333MA01	GCM219R72A333MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.25mm to 0.95mm
GCM32MR72A363KA01	GCM21BR72A473KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.25mm to 1.35mm ·Capacitance:36000pF to 47000pF
GCM32MR72A363MA01	GCM21BR72A473MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.25mm to 1.35mm ·Capacitance:36000pF to 47000pF
GCM32MR72A393KA01	GCM219R72A393KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.25mm to 0.95mm
GCM32MR72A393MA01	GCM219R72A393MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.25mm to 0.95mm
GCM32MR72A433KA01	GCM21BR72A473KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.25mm to 1.35mm ·Capacitance:43000pF to 47000pF
GCM32MR72A433MA01	GCM21BR72A473MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.25mm to 1.35mm ·Capacitance:43000pF to 47000pF
GCM32MR72A473KA01	GCM21BR72A473KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.25mm to 1.35mm
GCM32MR72A473MA01	GCM21BR72A473MA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.25mm to 1.35mm
GCM32NR72A513KA01	GCM21BR72A104KA37	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 2012M(0805inch) ·T size(Max):1.50mm to 1.35mm ·Capacitance:51000pF to 100000pF

GCM32NR72A513MA01	GCM21BR72A104MA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm •Capacitance:51000pF to 100000pF
GCM32NR72A563KA01	GCM21BR72A563KA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm
GCM32NR72A563MA01	GCM21BR72A563MA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm
GCM32NR72A683KA01	GCM21BR72A683KA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm
GCM32NR72A683KA51	GCM21BR72A683KA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm
GCM32NR72A683MA01	GCM21BR72A683MA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm
GCM32NR72A753KA01	GCM21BR72A104KA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm •Capacitance:75000pF to 100000pF
GCM32NR72A753MA01	GCM21BR72A104MA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm •Capacitance:75000pF to 100000pF
GCM32NR72A823KA01	GCM21BR72A823KA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm
GCM32NR72A823MA01	GCM21BR72A823MA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm
GCM32NR72A104KA01	GCM21BR72A104KA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm
GCM32NR72A104KA02	GCM21BR72A104KA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm
GCM32NR72A104KA51	GCM21BR72A104KA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm
GCM32NR72A104MA01	GCM21BR72A104MA37	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.50mm to 1.35mm
GRM32NB11C155KA01	GRM155R61C225KE11	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.50mm to 0.70mm • Temperature characteristics:B to X5R •Capacitance:1.5uF to 2.2uF
GRM32NB11C155KA01	GRM155R61C225KE11	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.50mm to 0.70mm • Temperature characteristics:B to X5R •Capacitance:1.5uF to 2.2uF
GRM32NB11C155KC01	GRM155R61C225KE11	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.50mm to 0.70mm • Temperature characteristics:B to X5R •Capacitance:1.5uF to 2.2uF
GRM32NB11C155MA01	GRM155R61C225ME11	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.50mm to 0.70mm • Temperature characteristics:B to X5R •Capacitance:1.5uF to 2.2uF
GRM32NB11C155MA01	GRM155R61C225ME11	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.50mm to 0.70mm • Temperature characteristics:B to X5R •Capacitance:1.5uF to 2.2uF

GRM32MB11C225KA01	GRM155R61C225KE11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.70mm • Temperature characteristics:B to X5R
GRM32MB11C225KC01	GRM155R61C225KE11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.70mm • Temperature characteristics:B to X5R
GRM32MB11C225MA01	GRM155R61C225ME11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.70mm • Temperature characteristics:B to X5R
GRM32NB11C335KA01	GRM185R61C475KE11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:3.3uF to 4.7uF
GRM32NB11C335KA01	GRM185R61C475KE11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:3.3uF to 4.7uF
GRM32NB11C335KC01	GRM185R61C475KE11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:3.3uF to 4.7uF
GRM32NB11C335MA01	GRM185R61C475ME11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:3.3uF to 4.7uF
GRM32NB11C335MA01	GRM185R61C475ME11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:3.3uF to 4.7uF
GRM329B11H623JA01	GRM155R61H104JE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:62000pF to 100000pF
GRM329B11H623KA01	GRM155R61H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:62000pF to 100000pF
GRM329B11H623KA01	GRM155R61H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:62000pF to 100000pF
GRM329B11H623MA01	GRM155R61H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:62000pF to 100000pF
GRM329B11H623MA01	GRM155R61H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:62000pF to 100000pF
GRM32MB11H913JA01	GRM155R61H104JE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:91000pF to 100000pF
GRM32MB11H913KA01	GRM155R61H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:91000pF to 100000pF
GRM32MB11H913KA01	GRM155R61H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:91000pF to 100000pF
GRM32MB11H913MA01	GRM155R61H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:91000pF to 100000pF
GRM32MB11H913MA01	GRM155R61H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:B to X5R • Capacitance:91000pF to 100000pF
GRM329B11H103JA01	GRM155R71H103JA88	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:B to X7R

GRM32NB11H564JA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:560000pF to 1.0uF • Capacitance Tolerance:+5% to +10%
GRM32NB11H564KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:560000pF to 1.0uF
GRM32NB11H564MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:560000pF to 1.0uF
GRM32NB11H564MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:560000pF to 1.0uF • Capacitance Tolerance:+20% to +10%
GRM32NB11H564MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:560000pF to 1.0uF • Capacitance Tolerance:+20% to +10%
GRM32NB11H684JA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:680000pF to 1.0uF • Capacitance Tolerance:+5% to +10%
GRM32NB11H684KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:680000pF to 1.0uF
GRM32NB11H684KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:680000pF to 1.0uF
GRM32NB11H684MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:680000pF to 1.0uF • Capacitance Tolerance:+20% to +10%
GRM32NB11H684MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:B to X7T • Capacitance:680000pF to 1.0uF • Capacitance Tolerance:+20% to +10%
GRM32NB31A226KE19	GRM31CR71A226KE15	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.80mm • Temperature characteristics:B to X7R
GRM32NB31A226KE19	GRM31CR71A226KE15	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.80mm • Temperature characteristics:B to X7R
GRM32NB31A226ME19	GRM31CR71A226ME15	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.80mm • Temperature characteristics:B to X7R
GRM32NB31A226ME19	GRM31CR71A226ME15	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.80mm • Temperature characteristics:B to X7R
GRM32NB31E685KA12	GRM188R61E106KA73	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:B to X5R • Capacitance:6.8uF to 10uF
GRM32NB31E685MA12	GRM188R61E106MA73	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:B to X5R • Capacitance:6.8uF to 10uF
GRM32NC81A226KE19	GRM31CR71A226KE15	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.80mm • Temperature characteristics:X6S to X7R
GRM32NC81A226ME19	GRM31CC71C226ME11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.90mm • Temperature characteristics:X6S to X7S • Rated Voltage:10V to 16V
GRM32NC81C226KE15	GRM31CC81E226KE11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.90mm • Rated Voltage:16V to 25V

GRM32NC81C226KE15	GRM31CC81E226KE11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.90mm • Rated Voltage:16V to 25V
GRM32NC81C226KE15	GRM31CC81E226KE11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.90mm • Rated Voltage:16V to 25V
GRM32NC81C226ME15	GRM31CC71C226ME11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.90mm • Temperature characteristics:X6S to X7S
GRM32ND70J226KE19	GRM188D70J226ME01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Capacitance Tolerance:±10% to ±20%
GRM32ND70J226ME19	GRM188D70J226ME01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm
GRM32ND71A226KE15	GRM31CR71A226KE15	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.80mm • Temperature characteristics:X7T to X7R
GRM32ND71A226ME15	GRM31CC71C226ME11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.90mm • Temperature characteristics:X7T to X7S • Rated Voltage:10V to 16V
GRM32NF11H684ZA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:F to X7T • Capacitance:680000pF to 1.0uF • Capacitance Tolerance: 20/80% to ±10%
GRM32MR11C225KA01	GRM21BR71E225KE11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.25mm to 1.40mm • Temperature characteristics:R to X7R • Rated Voltage:16V to 25V
GRM32MR11C225KC01	GRM21BR71E225KE11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.25mm to 1.40mm • Temperature characteristics:R to X7R • Rated Voltage:16V to 25V
GRM32MR11C225MA01	GRM21BR71E225ME11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.25mm to 1.40mm • Temperature characteristics:R to X7R • Rated Voltage:16V to 25V
GRM32NR11C335KA01	GRM21BR71C475KE51	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.50mm to 1.40mm • Temperature characteristics:R to X7R • Capacitance:3.3uF to 4.7uF
GRM32NR11C335KA01	GRM21BR71C475KE51	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.50mm to 1.40mm • Temperature characteristics:R to X7R • Capacitance:3.3uF to 4.7uF
GRM32NR11C335KC01	GRM21BR71C475KE51	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.50mm to 1.40mm • Temperature characteristics:R to X7R • Capacitance:3.3uF to 4.7uF
GRM32NR11C335MA01	GRM21BR71C475ME51	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.50mm to 1.40mm • Temperature characteristics:R to X7R • Capacitance:3.3uF to 4.7uF
GRM329R11H623JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:62000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R11H623KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:62000pF to 100000pF
GRM329R11H623MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:62000pF to 100000pF
GRM32MR11H913JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:91000pF to 100000pF • Capacitance Tolerance:±5% to ±10%

GRM329R11H163MA01	GRM155R71H223MA12	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:16000pF to 22000pF
GRM329R11H183JA01	GRM155R71H223JA12	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:18000pF to 22000pF
GRM329R11H183KA01	GRM155R71H223KA12	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:18000pF to 22000pF
GRM329R11H183MA01	GRM155R71H223MA12	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:18000pF to 22000pF
GRM329R11H203JA01	GRM155R71H223JA12	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:20000pF to 22000pF
GRM329R11H203KA01	GRM155R71H223KA12	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:20000pF to 22000pF
GRM329R11H203MA01	GRM155R71H223MA12	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:20000pF to 22000pF
GRM329R11H223JA01	GRM155R71H223JA12	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GRM329R11H223KA01	GRM155R71H223KA12	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GRM329R11H223MA01	GRM155R71H223MA12	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GRM329R11H243JA01	GRM21BR72A473JA01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0605inch) •T size(Max):1.00mm to 1.35mm • Temperature characteristics:R to X7R •Rated Voltage:50V to 100V •Capacitance:24000pF to 47000pF
GRM329R11H243KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:24000pF to 47000pF
GRM329R11H243MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:24000pF to 47000pF
GRM329R11H273JA01	GRM21BR72A473JA01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0605inch) •T size(Max):1.00mm to 1.35mm • Temperature characteristics:R to X7R •Rated Voltage:50V to 100V •Capacitance:27000pF to 47000pF
GRM329R11H273KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:27000pF to 47000pF
GRM329R11H273MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:27000pF to 47000pF
GRM329R11H303JA01	GRM21BR72A473JA01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0605inch) •T size(Max):1.00mm to 1.35mm • Temperature characteristics:R to X7R •Rated Voltage:50V to 100V •Capacitance:30000pF to 47000pF
GRM329R11H303KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:30000pF to 47000pF
GRM329R11H303MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R •Capacitance:30000pF to 47000pF

GRM329R11H333JA01	GRM21BR72A473JA01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.00mm to 1.35mm • Temperature characteristics:R to X7R • Rated Voltage:50V to 100V • Capacitance:33000pF to 47000pF
GRM329R11H333KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:33000pF to 47000pF
GRM329R11H333MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:33000pF to 47000pF
GRM329R11H363JA01	GRM21BR72A473JA01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.00mm to 1.35mm • Temperature characteristics:R to X7R • Rated Voltage:50V to 100V • Capacitance:36000pF to 47000pF
GRM329R11H363KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:36000pF to 47000pF
GRM329R11H363MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:36000pF to 47000pF
GRM329R11H393JA01	GRM21BR72A473JA01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.00mm to 1.35mm • Temperature characteristics:R to X7R • Rated Voltage:50V to 100V • Capacitance:39000pF to 47000pF
GRM329R11H393KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:39000pF to 47000pF
GRM329R11H393MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:39000pF to 47000pF
GRM329R11H433JA01	GRM21BR72A473JA01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.00mm to 1.35mm • Temperature characteristics:R to X7R • Rated Voltage:50V to 100V • Capacitance:43000pF to 47000pF
GRM329R11H433KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:43000pF to 47000pF
GRM329R11H433MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:43000pF to 47000pF
GRM329R11H473JA01	GRM21BR72A473JA01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.00mm to 1.35mm • Temperature characteristics:R to X7R • Rated Voltage:50V to 100V
GRM329R11H473KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GRM329R11H473MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R
GRM329R11H513JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:51000pF to 100000pF • Capacitance Tolerance:+5% to +10%
GRM329R11H513KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:51000pF to 100000pF
GRM329R11H513MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:51000pF to 100000pF

GRM329R11H563JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:56000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R11H563KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:56000pF to 100000pF
GRM329R11H563MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:56000pF to 100000pF
GRM329R11H683JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:68000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R11H683KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:68000pF to 100000pF
GRM329R11H683MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:68000pF to 100000pF
GRM32MR11H753JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:75000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM32MR11H753KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:75000pF to 100000pF
GRM32MR11H753MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:75000pF to 100000pF
GRM32MR11H823JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:82000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM32MR11H823KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:82000pF to 100000pF
GRM32MR11H823MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance:82000pF to 100000pF
GRM32MR11H104JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
GRM32MR11H104KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R
GRM32MR11H104MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Temperature characteristics:R to X7R
GRM32MR11H114JA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.87mm • Temperature characteristics:R to X7R • Capacitance:110000pF to 220000pF • Capacitance Tolerance:±5% to ±10%
GRM32MR11H114KA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.87mm • Temperature characteristics:R to X7R • Capacitance:110000pF to 220000pF

GRM32NR11H204MA01	GRM188R71H224MAC4	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R •Capacitance:200000pF to 220000pF
GRM32NR11H224JA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
GRM32NR11H224KA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R
GRM32NR11H224KA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R
GRM32NR11H224MA01	GRM188R71H224MAC4	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.87mm • Temperature characteristics:R to X7R
GRM32MR11H394JA01	GRM21BR71H474KA88	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.25mm to 1.35mm • Temperature characteristics:R to X7R •Capacitance:390000pF to 470000pF • Capacitance Tolerance:±5% to ±10%
GRM32MR11H394KA01	GRM21BR71H474KA88	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.25mm to 1.35mm • Temperature characteristics:R to X7R •Capacitance:390000pF to 470000pF
GRM32MR11H394MA01	GRM21BR71H474MA88	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.25mm to 1.35mm • Temperature characteristics:R to X7R •Capacitance:390000pF to 470000pF
GRM32MR11H434JA01	GRM21BR71H474KA88	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.25mm to 1.35mm • Temperature characteristics:R to X7R •Capacitance:430000pF to 470000pF • Capacitance Tolerance:±5% to ±10%
GRM32MR11H434KA01	GRM21BR71H474KA88	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.25mm to 1.35mm • Temperature characteristics:R to X7R •Capacitance:430000pF to 470000pF
GRM32MR11H434MA01	GRM21BR71H474MA88	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.25mm to 1.35mm • Temperature characteristics:R to X7R •Capacitance:430000pF to 470000pF
GRM32MR11H474JA01	GRM21BR71H474KA88	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.25mm to 1.35mm • Temperature characteristics:R to X7R • Capacitance Tolerance:±5% to ±10%
GRM32MR11H474KA01	GRM21BR71H474KA88	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.25mm to 1.35mm • Temperature characteristics:R to X7R
GRM32MR11H474KA01	GRM21BR71H474KA88	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.25mm to 1.35mm • Temperature characteristics:R to X7R
GRM32MR11H474MA01	GRM21BR71H474MA88	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 2012M(0805inch) •T size(Max):1.25mm to 1.35mm • Temperature characteristics:R to X7R
GRM32NR11H564JA01	GRM188D71H105KE01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 1.00mm • Temperature characteristics:R to X7T •Capacitance:560000pF to 1.0uF • Capacitance Tolerance:±5% to ±10%
GRM32NR11H564KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 1.00mm • Temperature characteristics:R to X7T •Capacitance:560000pF to 1.0uF
GRM32NR11H564MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 1.00mm • Temperature characteristics:R to X7T •Capacitance:560000pF to 1.0uF
GRM32NR11H684JA01	GRM188D71H105KE01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 1.00mm • Temperature characteristics:R to X7T •Capacitance:680000pF to 1.0uF • Capacitance Tolerance:±5% to ±10%

GRM32NR11H684KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:680000pF to 1.0uF
GRM32NR11H684KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:680000pF to 1.0uF
GRM32NR11H684MA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 1.00mm • Temperature characteristics:R to X7T • Capacitance:680000pF to 1.0uF • Capacitance Tolerance:±20% to ±10%
GRM32NR61A226KE19	GRM31CR71A226KE15	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.80mm • Temperature characteristics:X5R to X7R
GRM32NR61A226ME19	GRM31CR71A226ME15	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 3216M(1206inch) • T size(Max):1.50mm to 1.80mm • Temperature characteristics:X5R to X7R
GRM32NR61E685KA12	GRM32ER71H106KA12	<ul style="list-style-type: none"> • T size(Max):1.50mm to 2.70mm • Temperature characteristics:X5R to X7R • Rated Voltage:25V to 50V • Capacitance:6.8uF to 10uF
GRM32NR61E685MA12	GRM32ER71H106MA12	<ul style="list-style-type: none"> • T size(Max):1.50mm to 2.70mm • Temperature characteristics:X5R to X7R • Rated Voltage:25V to 50V • Capacitance:6.8uF to 10uF
GRM32MR71C225KA01	GRM21BR71E225KE11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.25mm to 1.40mm • Rated Voltage:16V to 25V
GRM32MR71C225KC01	GRM21BR71E225KE11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.25mm to 1.40mm • Rated Voltage:16V to 25V
GRM32MR71C225MA01	GRM21BR71E225ME11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.25mm to 1.40mm • Rated Voltage:16V to 25V
GRM32NR71C335KA01	GRM21BR71C475KE51	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.50mm to 1.40mm • Capacitance:3.3uF to 4.7uF
GRM32NR71C335KC01	GRM21BR71C475KE51	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.50mm to 1.40mm • Capacitance:3.3uF to 4.7uF
GRM32NR71C335KC27	GRM21BR71C475KE51	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.50mm to 1.40mm • Capacitance:3.3uF to 4.7uF
GRM32NR71C335MA01	GRM21BR71C475ME51	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.50mm to 1.40mm • Capacitance:3.3uF to 4.7uF
GRM32NR71E155KA01	GRM21BR71E225KE11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.50mm to 1.40mm • Capacitance:1.5uF to 2.2uF
GRM32NR71E155MA01	GRM21BR71E225ME11	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 2012M(0805inch) • T size(Max):1.50mm to 1.40mm • Capacitance:1.5uF to 2.2uF
GRM329R71H623JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:62000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R71H623JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:62000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R71H623KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:62000pF to 100000pF

GRM329R71H623MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:62000pF to 100000pF
GRM32MR71H913JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.25mm to 0.55mm ·Capacitance:91000pF to 100000pF ·Capacitance Tolerance:±5% to ±10%
GRM32MR71H913JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.25mm to 0.55mm ·Capacitance:91000pF to 100000pF ·Capacitance Tolerance:±5% to ±10%
GRM32MR71H913KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.25mm to 0.55mm ·Capacitance:91000pF to 100000pF
GRM32MR71H913MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.25mm to 0.55mm ·Capacitance:91000pF to 100000pF
GRM329R71H103JA01	GRM155R71H103JA88	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GRM329R71H103KA01	GRM155R71H103KA88	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GRM329R71H103MA01	GRM155R71H103MA88	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm
GRM329R71H113JA01	GRM155R71H223JA12	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:11000pF to 22000pF
GRM329R71H113KA01	GRM155R71H223KA12	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:11000pF to 22000pF
GRM329R71H113MA01	GRM155R71H223MA12	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:11000pF to 22000pF
GRM329R71H123JA01	GRM155R71H223JA12	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:12000pF to 22000pF
GRM329R71H123KA01	GRM155R71H223KA12	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:12000pF to 22000pF
GRM329R71H123MA01	GRM155R71H223MA12	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:12000pF to 22000pF
GRM329R71H133JA01	GRM155R71H223JA12	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:13000pF to 22000pF
GRM329R71H133KA01	GRM155R71H223KA12	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:13000pF to 22000pF
GRM329R71H133MA01	GRM155R71H223MA12	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:13000pF to 22000pF
GRM329R71H153JA01	GRM155R71H223JA12	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:15000pF to 22000pF
GRM329R71H153KA01	GRM155R71H223KA12	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1005M(0402inch) ·T size(Max):1.00mm to 0.55mm ·Capacitance:15000pF to 22000pF

GRM329R71H153MA01	GRM155R71H223MA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:15000pF to 22000pF
GRM329R71H163JA01	GRM155R71H223JA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:16000pF to 22000pF
GRM329R71H163KA01	GRM155R71H223KA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:16000pF to 22000pF
GRM329R71H163MA01	GRM155R71H223MA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:16000pF to 22000pF
GRM329R71H183JA01	GRM155R71H223JA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:18000pF to 22000pF
GRM329R71H183KA01	GRM155R71H223KA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:18000pF to 22000pF
GRM329R71H183MA01	GRM155R71H223MA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:18000pF to 22000pF
GRM329R71H203JA01	GRM155R71H223JA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:20000pF to 22000pF
GRM329R71H203KA01	GRM155R71H223KA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:20000pF to 22000pF
GRM329R71H203MA01	GRM155R71H223MA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:20000pF to 22000pF
GRM329R71H223JA01	GRM155R71H223JA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm
GRM329R71H223JA26	GRM155R71H223JA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm
GRM329R71H223KA01	GRM155R71H223KA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm
GRM329R71H223MA01	GRM155R71H223MA12	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm
GRM329R71H243JA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:24000pF to 47000pF • Capacitance Tolerance:±5% to ±10%
GRM329R71H243JA26	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:24000pF to 47000pF • Capacitance Tolerance:±5% to ±10%
GRM329R71H243KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:24000pF to 47000pF
GRM329R71H243MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:24000pF to 47000pF
GRM329R71H273JA01	GRM155R71H473KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:27000pF to 47000pF • Capacitance Tolerance:±5% to ±10%

GRM329R71H433JA01	GRM155R71H473KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:43000pF to 47000pF • Capacitance Tolerance:±5% to ±10%
GRM329R71H433JA26	GRM155R71H473KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:43000pF to 47000pF • Capacitance Tolerance:±5% to ±10%
GRM329R71H433KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:43000pF to 47000pF
GRM329R71H433MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:43000pF to 47000pF
GRM329R71H473JA01	GRM155R71H473KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Capacitance Tolerance:±5% to ±10%
GRM329R71H473JA26	GRM155R71H473KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm • Capacitance Tolerance:±5% to ±10%
GRM329R71H473KA01	GRM155R71H473KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm
GRM329R71H473MA01	GRM155R71H473ME14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm
GRM329R71H513JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:51000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R71H513JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:51000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R71H513KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:51000pF to 100000pF
GRM329R71H513MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:51000pF to 100000pF
GRM329R71H563JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:56000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R71H563JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:56000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R71H563KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:56000pF to 100000pF
GRM329R71H563MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:56000pF to 100000pF
GRM329R71H683JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:68000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R71H683JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:68000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R71H683KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1005M(0402inch) •T size(Max):1.00mm to 0.55mm •Capacitance:68000pF to 100000pF

GRM329R71H683MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.00mm to 0.55mm • Capacitance:68000pF to 100000pF
GRM32MR71H753JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:75000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM32MR71H753JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:75000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM32MR71H753KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:75000pF to 100000pF
GRM32MR71H753MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:75000pF to 100000pF
GRM32MR71H823JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:82000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM32MR71H823JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:82000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM32MR71H823KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:82000pF to 100000pF
GRM32MR71H823MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance:82000pF to 100000pF
GRM32MR71H104JA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance Tolerance:±5% to ±10%
GRM32MR71H104JA26	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm • Capacitance Tolerance:±5% to ±10%
GRM32MR71H104KA01	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm
GRM32MR71H104KA26	GRM155R71H104KE14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm
GRM32MR71H104MA01	GRM155R71H104ME14	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1005M(0402inch) • T size(Max):1.25mm to 0.55mm
GRM32MR71H114JA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.87mm • Capacitance:110000pF to 220000pF • Capacitance Tolerance:±5% to ±10%
GRM32MR71H114JA26	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.87mm • Capacitance:110000pF to 220000pF • Capacitance Tolerance:±5% to ±10%
GRM32MR71H114KA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.87mm • Capacitance:110000pF to 220000pF
GRM32MR71H114MA01	GRM188R71H224MAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.87mm • Capacitance:110000pF to 220000pF
GRM32NR71H124JA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Capacitance:120000pF to 220000pF • Capacitance Tolerance:±5% to ±10%

GRM32NR71H204JA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Capacitance:200000pF to 220000pF • Capacitance Tolerance:±5% to ±10%
GRM32NR71H204KA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Capacitance:200000pF to 220000pF
GRM32NR71H204KA26	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Capacitance:200000pF to 220000pF
GRM32NR71H204MA01	GRM188R71H224MAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Capacitance:200000pF to 220000pF
GRM32NR71H224JA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm • Capacitance Tolerance:±5% to ±10%
GRM32NR71H224KA01	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm
GRM32NR71H224KA26	GRM188R71H224KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm
GRM32NR71H224MA01	GRM188R71H224MAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.50mm to 0.87mm
GRM32MR71H394JA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:390000pF to 1.0uF • Capacitance Tolerance:±5% to ±10%
GRM32MR71H394JA26	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:390000pF to 1.0uF • Capacitance Tolerance:±5% to ±10%
GRM32MR71H394KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:390000pF to 1.0uF
GRM32MR71H394KA26	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:390000pF to 1.0uF
GRM32MR71H394MA01	GRM188D71H105ME01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:390000pF to 1.0uF
GRM32MR71H434JA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:430000pF to 1.0uF • Capacitance Tolerance:±5% to ±10%
GRM32MR71H434KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:430000pF to 1.0uF
GRM32MR71H434KA26	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:430000pF to 1.0uF
GRM32MR71H434MA01	GRM188D71H105ME01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:430000pF to 1.0uF
GRM32MR71H474JA01	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:470000pF to 1.0uF • Capacitance Tolerance:±5% to ±10%
GRM32MR71H474JA26	GRM188D71H105KE01	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T • Capacitance:470000pF to 1.0uF • Capacitance Tolerance:±5% to ±10%

GRM32MR71H474KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T •Capacitance:470000pF to 1.0uF
GRM32MR71H474KA26	GRM188D71H105KE01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T •Capacitance:470000pF to 1.0uF
GRM32MR71H474MA01	GRM188D71H105ME01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.25mm to 1.00mm • Temperature characteristics:X7R to X7T •Capacitance:470000pF to 1.0uF
GRM32NR71H564JA01	GRM188D71H105KE01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 1.00mm • Temperature characteristics:X7R to X7T •Capacitance:560000pF to 1.0uF • Capacitance Tolerance:±5% to ±10%
GRM32NR71H564KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 1.00mm • Temperature characteristics:X7R to X7T •Capacitance:560000pF to 1.0uF
GRM32NR71H564KA36	GRM188D71H105KE01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 1.00mm • Temperature characteristics:X7R to X7T •Capacitance:560000pF to 1.0uF
GRM32NR71H564MA01	GRM188D71H105ME01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 1.00mm • Temperature characteristics:X7R to X7T •Capacitance:560000pF to 1.0uF
GRM32NR71H684JA01	GRM188D71H105KE01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 1.00mm • Temperature characteristics:X7R to X7T •Capacitance:680000pF to 1.0uF • Capacitance Tolerance:±5% to ±10%
GRM32NR71H684KA01	GRM188D71H105KE01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 1.00mm • Temperature characteristics:X7R to X7T •Capacitance:680000pF to 1.0uF
GRM32NR71H684KA36	GRM188D71H105KE01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 1.00mm • Temperature characteristics:X7R to X7T •Capacitance:680000pF to 1.0uF
GRM32NR71H684MA01	GRM188D71H105ME01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 1.00mm • Temperature characteristics:X7R to X7T •Capacitance:680000pF to 1.0uF
GRM32NR72A623JA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:62000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM32NR72A623KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:62000pF to 100000pF
GRM32NR72A623MA01	GRM188R72A104MA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:62000pF to 100000pF
GRM32NR72A913JA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:91000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM32NR72A913KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:91000pF to 100000pF
GRM32NR72A913MA01	GRM188R72A104MA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:91000pF to 100000pF
GRM329R72A103JA01	GRM188R72A103JA01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.00mm to 0.87mm
GRM329R72A103KA01	GRM188R72A103KA01	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.00mm to 0.87mm

GRM329R72A183MA01	GRM188R72A223MAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.87mm • Capacitance:18000pF to 22000pF
GRM329R72A203JA01	GRM188R72A223JAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.87mm • Capacitance:20000pF to 22000pF
GRM329R72A203KA01	GRM188R72A223KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.87mm • Capacitance:20000pF to 22000pF
GRM329R72A203MA01	GRM188R72A223MAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.87mm • Capacitance:20000pF to 22000pF
GRM329R72A223JA01	GRM188R72A223JAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.87mm
GRM329R72A223KA01	GRM188R72A223KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.87mm
GRM329R72A223KA01	GRM188R72A223KAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.87mm
GRM329R72A223MA01	GRM188R72A223MAC4	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.87mm
GRM329R72A243JA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.90mm • Capacitance:24000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R72A243KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.90mm • Capacitance:24000pF to 100000pF
GRM329R72A243MA01	GRM188R72A104MA35	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.90mm • Capacitance:24000pF to 100000pF
GRM329R72A273JA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.90mm • Capacitance:27000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R72A273KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.90mm • Capacitance:27000pF to 100000pF
GRM329R72A273MA01	GRM188R72A104MA35	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.90mm • Capacitance:27000pF to 100000pF
GRM329R72A303JA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.90mm • Capacitance:30000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM329R72A303KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.90mm • Capacitance:30000pF to 100000pF
GRM329R72A303MA01	GRM188R72A104MA35	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.00mm to 0.90mm • Capacitance:30000pF to 100000pF
GRM32MR72A333JA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.90mm • Capacitance:33000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM32MR72A333KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> • LW size:3225M(1210inch) to 1608M(0603inch) • T size(Max):1.25mm to 0.90mm • Capacitance:33000pF to 100000pF

GRM32NR72A563JA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:56000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM32NR72A563KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:56000pF to 100000pF
GRM32NR72A563KA26	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:56000pF to 100000pF
GRM32NR72A563MA01	GRM188R72A104MA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:56000pF to 100000pF
GRM32NR72A683JA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:68000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM32NR72A683KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:68000pF to 100000pF
GRM32NR72A683KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:68000pF to 100000pF
GRM32NR72A683KA26	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:68000pF to 100000pF
GRM32NR72A683MA01	GRM188R72A104MA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:68000pF to 100000pF
GRM32NR72A753JA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:75000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM32NR72A753KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:75000pF to 100000pF
GRM32NR72A753MA01	GRM188R72A104MA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:75000pF to 100000pF
GRM32NR72A823JA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:82000pF to 100000pF • Capacitance Tolerance:±5% to ±10%
GRM32NR72A823KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:82000pF to 100000pF
GRM32NR72A823MA01	GRM188R72A104MA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm •Capacitance:82000pF to 100000pF
GRM32NR72A104JA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm • Capacitance Tolerance:±5% to ±10%
GRM32NR72A104KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm
GRM32NR72A104KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm
GRM32NR72A104KA01	GRM188R72A104KA35	<ul style="list-style-type: none"> •LW size:3225M(1210inch) to 1608M(0603inch) •T size(Max):1.50mm to 0.90mm

GRM32NR72A104KA26	GRM188R72A104KA35	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.90mm
GRM32NR72A104MA01	GRM188R72A104MA35	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 0.90mm
GRM32MR72A474KA01	GRM188D72A105KE01	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.25mm to 1.00mm · Temperature characteristics:X7R to X7T ·Capacitance:470000pF to 1.0uF
GRM32MR72A474MA01	GRM188D72A105ME01	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.25mm to 1.00mm · Temperature characteristics:X7R to X7T ·Capacitance:470000pF to 1.0uF
GRM32CR72A684KA01	GRM188D72A105KE01	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.80mm to 1.00mm · Temperature characteristics:X7R to X7T ·Capacitance:680000pF to 1.0uF
GRM32CR72A684MA01	GRM188D72A105KE01	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.80mm to 1.00mm · Temperature characteristics:X7R to X7T ·Capacitance:680000pF to 1.0uF · Capacitance Tolerance:±20% to ±10%
GRM32CR72A105KA35	GRM188D72A105KE01	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.80mm to 1.00mm · Temperature characteristics:X7R to X7T
GRM32CR72A105KA35	GRM188D72A105KE01	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.80mm to 1.00mm · Temperature characteristics:X7R to X7T
GRM32CR72A105MA35	GRM188D72A105KE01	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.80mm to 1.00mm · Temperature characteristics:X7R to X7T · Capacitance Tolerance:±20% to ±10%
GRT32NC81A226KE01	GRT31CC81C226KE01	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 3216M(1206inch) ·T size(Max):1.50mm to 1.80mm ·Rated Voltage:10V to 16V
GRT32NC81A226ME01	GRT31CC81C226ME01	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 3216M(1206inch) ·T size(Max):1.50mm to 1.80mm ·Rated Voltage:10V to 16V
GRT32NR61A226KE01	GRT188R61A226ME13	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 1.00mm · Capacitance Tolerance:±10% to ±20%
GRT32NR61A226ME01	GRT188R61A226ME13	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 1608M(0603inch) ·T size(Max):1.50mm to 1.00mm
GRT32NR61E685KE01	GRT31MR61C685KE01	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 3216M(1206inch) ·T size(Max):1.50mm to 1.25mm ·Rated Voltage:25V to 16V
GRT32NR61E685ME01	GRT31MR61C685KE01	<ul style="list-style-type: none"> ·LW size:3225M(1210inch) to 3216M(1206inch) ·T size(Max):1.50mm to 1.25mm ·Rated Voltage:25V to 16V · Capacitance Tolerance:±20% to ±10%